


17
JM
WVF 17

TOTAL HEAD			PERFORMANCE CURVE		3500 RPM		1.0 S.G. 70°F		PUMP 17		
MTRS	PSI	FEET	NUMBER	40.000.416			60 Hz		PUMP SIZE: 2.0 x 2.0 x 5.5 IMP. TYPE: ENCLOSED MAX. DIA.: 5.50 IMPELLER NO.: C1155A MAX. SPHERE: 11/32 PEICL: 0.92		
55	78	180									
49	69	160									
43	61	140									
37	52	120									
30	43	100									
24	35	80									
18	26	60									
12	17	40									
6	9	20									
			0 40 80 120 160 200 240 0 9 18 27 36 45 54								

017WVFJM
81.001.994 M19

WVF 17 • Iron • JM Frame • 3500 RPM

E017JM14WVF



KEY NO.	PART NAME	WVF 17
1	CASE, IRON, 2 X 2 NPT Requires Suction Fitting (Key #F), and Suction Gasket, Key #73A	130.000.168X
2	IMPELLER, 7/8" KEYED, ENCLOSED, SPECIFY DIAMETER: CIBF IRON BRONZE	131.000.823 137.000.128 131.000.806
4	MOTOR: JM140/180	See Chart
14*	SHAFT SLEEVE BRONZE STAINLESS	110.000.178 110.000.192
26*	IMPELLER RETAINER, STAINLESS	118.000.111A
32*	KEY, STAINLESS	102.000.102
38*	O-RING, SHAFT BUNA VITON	116.000.117 116.000.105
40*	FLINGER, STAINLESS	104.000.165
57	FLANGE, IRON, 5½" x 5½" Includes Flange Gasket (Key #73B), Set Screws and Plugs	132.000.206X
71	ADAPTER, IRON JM140/180	132.000.194X
73*	GASKET, CASE, BUNA	116.000.146
73A	GASKET, CASE SUCTION, BUNA	116.000.148
73B	GASKET, FLANGE	116.000.156
89*	1½" SEALS: TYPE 21, BN-CARB/CM TYPE 21, VN-CARB/CM TYPE 21, VN-CARB/SIL TYPE 21, EPDM-CARB/SIL	101.000.168 101.000.194 101.000.175 101.000.175B
89A*	SEAL RETAINER	104.000.175
F	FITTING, SUCTION 2.5 TRN X 2 NPT	110.000.209
--	REPAIR KITS: BN-CARB/CM SEAL VN-CARB/CM (S) SEAL VN-CARB/SIL SEAL EPDM-CARB/SIL SEAL	118.000.343 118.000.343A 118.000.343B 118.000.343D

* DENOTES COMPONENTS INCLUDED IN REPAIR KIT.
ALL REPAIR KITS INCLUDE THE BRONZE SHAFT SLEEVE EXCEPT
THE (S) INDICATED, WHICH IS STAINLESS WITH VITON SHAFT O-RING.