

SCOT


MOTORPUMP™ — 3500 RPM 60 HERTZ, 5" FLANGE X 1.25 NPT

126
J56
WVF 126


MOTOR DIMENSIONS NEMA J56 FRAME 3500 RPM 3 PHASE ODP

HP	FRAME	L	O
.5	J56	8.31	6.50
.75, 1	J56	8.31	6.50
2	J56	9.31	6.50
3	J56	9.31	6.50

D126J56WVF_PRINT DRAWING DEPICTS 56J 3PHASE ODP MOTOR




ALL DIMENSIONS IN INCHES



D126J56WVF 1263500
0607WVF

126
J56
WVF 126

126WVFJ56
81.001.199 M19

WVF 126 • Iron • J56 Frame • 3500 RPM

KEY NO.	PART NAME	WVF 126	
1	CASE, IRON, 2.5 TRN x 1.25 NPT Includes Suction Gasket, Key #73A	137.002.410X	
	4.00	131.000.763J	
	4.50	131.000.763E	
	4.88	131.000.763D	
	5.00	131.000.763C	
	5.25	131.000.763B	
	5.50	131.000.763H	
	5.63	131.000.763A	
4	MOTOR: J56, ROUND BODY J56, 3.5" RIGID BASE	See Chart See Chart	
4A	DRIP COVER Varies by motor manufacturer	Contact Factory	
24*	NUT, STAINLESS Not Required on 1/3-1-1/2HP 1Phase Motors	105.000.465	
30*	D WASHER, STAINLESS Not Required on 1/3-1-1/2HP 1Phase Motors	104.000.168	
40*	FLINGER, NEOPRENE	104.000.171	
57	FLANGE, IRON, 5" x 5" Includes Flange Gasket Key #73B, Set Screws and Plugs	132.000.206X	
71	ADAPTER, IRON	132.000.337X	
73*	GASKET, CASE, BUNA	116.000.146	
73A	GASKET, CASE SUCTION, BUNA	116.000.148	
73B	GASKET, FLANGE	116.000.156	
89*	5/8" SEALS:		
	NO RETAINER: (not shown)		
	TYPE 6, BN-CARB/CM	101.000.110	
	WITH RETAINER:		
	TYPE 21, VN-CARB/CM	101.000.103	
	TYPE 21, VN-CARB/SIL	101.000.120	
	TYPE 21, VN-SIL/SIL	101.000.239	
--	REPAIR KITS:	3 PHASE: 2 & 3HP 1PH	1 PHASE: 1/3 - 1-1/2HP
	BN-CARB/CM SEAL	118.000.340	118.000.340.1
	VN-CARB/CM SEAL	118.000.340A	118.000.340A.1
	VN-CARB/SIL SEAL	118.000.340B	118.000.340B.1
	VN-SIL/SIL SEAL	118.000.340J	118.000.340J.1
	EPDM-CARB/SIL SEAL	118.000.340C	118.000.340C.1
	EPDM-SIL/SIL SEAL	118.000.340D	118.000.340D.1
* DENOTES COMPONENTS INCLUDED IN REPAIR KIT. USE 3 PHASE KIT ON 2-3 HP 1 PHASE MOTORS.			